Fittings Catalog



Air Conditioning & Heating Replacement Parts



Fittings

| Aeroquip E-Z Clip Fittings & | |
|--|----|
| Hoses | 3 |
| Accessories | 3 |
| Hoses | 4 |
| Lifesaver Braze Nipple Fitting | 5 |
| Female O-Ring Fittings | 5 |
| Bulkhead Fitting | 5 |
| Female O-Ring Pilot Fittings | 6 |
| Male O-Ring Fittings | 8 |
| Male Splicer Fittings | 9 |
| Female O-Ring Fittings | 10 |
| AIR-O-CRIMP Fittings | 10 |
| Male O-Ring Fittings | 12 |
| Splicer Fittings | 14 |
| Weld-On Fittings | 16 |
| AIR-O-CRIMP Assembly | 17 |
| ATCO Beadlock Fittings | 18 |
| Accessories | 18 |
| Goodyear (Galaxy) Hoses | 18 |
| Compression Fittings - Standard Barrier | |
| Female Flare Fittings - Standard Barrier | 20 |
| Female O-Ring Fittings - Reduced | |
| Barrier | 23 |
| Male Insert O-Ring Fittings - Standard | |
| Barrier | 24 |
| Male O-Ring Fittings - Standard Barrier | 25 |
| Male O-Ring Fittings - Reduced Barrier | 26 |
| Splicer Fittings - Standard Barrier | 27 |
| Splicer Fittings - Reduced Barrier | 27 |
| Weld-On Fittings - Standard Barrier | 27 |
| Weld-On Fittings - Reduced Barrier | 28 |
| Beadlock Fitting Identification | 30 |
| Male O-Ring | 31 |
| Female O-Ring | 31 |
| Male Insert O-Ring | 31 |
| O-Rings | 31 |
| Female Flare | 32 |
| Male Flare | 32 |
| Hose End Sizes | 32 |
| Torque Recommendations | 32 |

| Refrigerant Hose Sizes Beadlock | 33 33 |
|---|----------|
| Torque Recommendations | 33 |
| Burgaflex Fittings | 34 |
| Goodyear (Galaxy) Hoses | 34 |
| Burgaflex Fittings - Standard Barrier | 35 |
| Burgaflex Crimp Fittings - Reduced Barrier | 36 |
| Burgaflex Crimp Fittings - Reduced Barrier | 37 |
| Burgaflex Accessories | 38 |
| Ferrule Fittings | 38 |
| r circle r mings | 00 |
| O-Rings | 39 |
| O-Rings Specifications | 40 |
| O-Ring Assortment Kits | 41 |
| O-Ring Rubber Material Data | 43 |
| | |
| Bulkhead Adapters, Tubing & D | |
| Hoses | 43 |
| Bulkhead Adapters | 43 |
| Drain Hose & Accessories | 44 45 |
| Insulation Tubing | 45 45 |
| Tube & Fitting Assembly | 45 |
| Ducting, Clamps & Hoses | 46 |
| Flexible Ducting | 46 |
| Hose Clamps | 46 |
| Hoses | 47 |
| | |
| Accessories | 47 |
| Wire Clips & Ties | 47 |
| • | |
























Accessories













Hoses









All hoses have the following bend radius:

| Hose Size: No. 6 | Minimum Bend Radius: 2" (50mm) |
|-------------------|------------------------------------|
| Hose Size: No. 8 | Minimum Bend Radius: 2 1/2" (63mm) |
| Hose Size: No. 10 | Minimum Bend Radius: 3" (76.2mm) |
| Hose Size: No. 12 | Minimum Bend Radius: 4" (101.6mm) |
| Hose Size: No. 16 | Minimum Bend Radius: 7" (177.8mm) |



Lifesaver Braze Nipple Fitting

Bulkhead Fitting





Female O-Ring Fittings









Female O-Ring Fittings (cont'd)









Female O-Ring Pilot Fittings









Female O-Ring Pilot Fittings (cont'd)











Male O-Ring Fittings
















Male O-Ring Fittings (cont'd)







Щ

Male Splicer Fittings





Splicer with High Side R134-a





Male Splicer Fittings (cont'd)






1

Female O-Ring Fittings











Female O-Ring Fittings (cont'd)



















Female O-Ring Fittings (cont'd)





Fitting Thread Size: 3/4"-16 Hose Size: No. 8 Fitting Size: No. 8 1000022164

Female 90 Degree O-Ring with 13mm Switch or Service Port Fitting with Clamp



| Fitting Size: No. 10 Fittin Thre Size: 7/8"- | Size: No. | 1000022514 |
|---|-----------|------------|
|---|-----------|------------|

Female 90 Degree O-Ring with 13mm Switch or Service Port Fitting with Clamp (Step Up)



| Fitting | Fitting | Hose | 1000022519 |
|-----------|---------|-----------|------------|
| Size: No. | Thread | Size: No. | |
| 10 | Size: | 12 | |

Male O-Ring Fittings

Straight Male Insert O-Ring Fitting with Clamp



| Fitting Size: No. 6 | Fitting Thread Size: 5/8"- 18 | Hose Size: No. 6 | 1000022945 |
|------------------------|--|------------------------|------------|
| Fitting Size: No. 8 | Fitting Thread Size: | Hose Size: No. | 1000022947 |

Straight Male O-Ring Fitting with Clamp



| Fitting Size: No. 6 | Thread Size: 5/8"- | Hose Size: No. 6 | 1000022648 |
|------------------------|----------------------------|------------------------|------------|
| Fitting Size: No. 8 | Fitting Thread Size: | Hose Size: No. 8 | 1000022746 |

Straight Male O-Ring Fitting with Clamp (Step Up)



| Fitting Size: No. 6 | Thread Size: 5/8"- 18 | Hose Size: No. 8 | 1000022704 | |
|----------------------------|---------------------------------------|-------------------------|------------|--|
| Fitting Size: No. 10 | Fitting Thread Size: 7/8"-14 | Hose Size: No. 12 | 1000022764 | |

Hose


Fitting

12


Male O-Ring Fittings (cont'd)

















Male O-Ring Fittings (cont'd)



1


Splicer Fittings










Splicer Fittings (cont'd)












Weld-On Fittings





AIR-O-CRIMP Assembly

Cut or trim the hose.

Cut or trim the hose to the desired length using the kwikcut hose cutter. The cut should be made square to the hose length.



Assemble the clamp.

Assemble the clamp assembly onto the hose with the locator tab positioned approximately where the fitting groove will be when the fitting is assembled.



Apply refrigerant oil.

Apply a small amount of refrigerant oil (PAG or Ester) to the fitting barb and o-rings (optional). Assmeble the fitting into the hose until hose touches the ramped step on the fitting. Adjust the clamp assembly so the tab on the locator "snaps" into the groove of the fitting.



Crimp clamps.

Using the air crimp gun or the manual crimp pliers, crimp each clamp separately.

Caution: If using the manual pliers, make sure that there is a metal to metal contact of the clamp ear when the crimp is made. There will be a slight amount of spring-back of the clamp ear when the crimp pliers are released. Failure to fully close the clamp may result in refrigerant leaks.



Locator comes off.

The locator will "pop off" after the second clamp is crimped and can be discarded. The result is a clean appearance and a reliable assembly.





Accessories

ATCO Hose Clamp Assembly (packaged in quantities of 10)



| Hose Size: No. 6 | Color: Red | 1000025384 |
|----------------------|---------------|------------|
| Hose Size: No. 8 | Color: Black | 1000025389 |
| Hose Size: No. 10 | Color: Yellow | 1000025392 |
| Hose Size: No. 12 | Color: | 1000197772 |
| Hose Size: No. 16 | Color: | 1000197779 |

Goodyear (Galaxy) Hoses

- This hose meets J2064 specification
- · Easy Couplability

Internal rubber layer makes coupling simple, assuring better assembly integrity while reducing the risk of refrigerant loss around the fittings.

• Reduced Ozone Permeation

Internal Nylon Barrier hose is specifically designed to reduce the permeation level of ozone depleting refrigerant and chemicals in heavy duty air conditioning systems.

• Universal Compatibility

Extensive testing has shown 4826 Barrier Hose to be compatible with R-12, R-134a and Ternary Blends.

• Low Volumetric Expansion

- Dimensionally Stable
- Flexible
- Easy to Route
- Reduction in Noise & Vibration
- J51 All Outside Diameters
- Tube: Polychloropene Barrier
- Reinforcement: Synthetic Yarn
- Cover: EPDM

NOTE: For use with steel or aluminum Push-On or Beadlock (Bubble Crimp) type fittings only!



Goodyear (Galaxy) Hoses (cont'd)

Goodyear (Galaxy) 4826 Hose for Standard Fitting









| Length: 50 Ft. | Hose Inner Diameter: 5/16" (7.9mm) | Hose Outer Diameter: 3/4" (19.1mm) | 550307 |
|--------------------|--|--|------------|
| Length: 50 Ft. | Hose Inner Diameter: 13/32" (10.3mm) | Hose Outer Diameter: 29/32" 23mm) | 550308 |
| Length: 50 Ft. | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 1" 25.4mm) | 550309 |
| Length: 50 Ft. | Hose Inner Diameter: 5/8" (15.9mm) | Hose Outer Diameter: 1 1/8" (28.6mm) | 550310 |
| Length: 825 Ft. | Hose Inner Diameter: 5/16" (7.9mm) | Hose Outer Diameter: 3/4" (19.1mm) | 1002300977 |
| Length: 725 Ft. | Hose Inner Diameter: 13/32" (10.3mm) | Hose Outer Diameter: 29/32" 23mm) | 1002301587 |
| Length: 700 Ft. | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 1" 25.4mm) | 1002301589 |
| | | | |

| Length: 50 Ft. | Hose Inner Diameter: 5/16" (7.9mm) | Hose Outer Diameter: 9/16" (14.7mm) | 1001639549 |
|--------------------|--|--|------------|
| Length: 50 Ft. | Hose Inner Diameter: 13/32" (10.3mm) | Hose Outer Diameter: 11/16" (17.3mm) | 1001639551 |
| Length: 50 Ft. | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 3/4" (19.4mm) | 1001639552 |
| Length: 50 Ft. | Hose Inner Diameter: 5/8" (15.9mm) | Hose Outer Diameter: 15/16" (23.6mm) | 1001639553 |
| Length: 825 Ft. | Hose Inner Diameter: 5/16" (7.9mm) | Hose Outer Diameter: 9/16" (14.7mm) | 1001260067 |
| Length: 725 Ft. | Hose Inner Diameter: 13/32" (10.3mm) | Hose Outer Diameter: 11/16" 17.3mm) | 1001260070 |
| Length: 600 Ft. | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 3/4" (19.4mm) | 1002300971 |
| Length: 600 Ft. | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 3/4" (19.4mm) | 1001260075 |
| Length: 425 Ft. | Hose Inner Diameter: 5/8" (15.9mm) | Hose Outer Diameter: 15/16" (23.6mm) | 1002300976 |
| | | | |

Hose Outer Diameter: 15/16" (23.6mm)

1001260076

Inner Diameter: 5/8" (15.9mm)

Length: 425 Ft.



Compression Fittings - Standard Barrier

| Straight Compression Fitting (Standard Barrier) | | | |
|---|---|-------------------------|--------|
| Fitting Size: No. 10 | Fitting Thread Size: 5/8" Tube | Hose Size: No. 10 | 550979 |
| Fitting Size: No. 12 | Fitting Thread Size: 3/4" Tube | Hose Size: No. 12 | 550980 |

Female Flare Fittings - Standard Barrier







Female O-Ring Fittings - Standard Barrier (cont'd)






Hose Size: 3/4"-16

B409087

Fitting Thread

Size: M10 x 1.25

Fitting Size: No. 8





Fitting Size: No. 8








Female O-Ring Fittings - Standard Barrier (cont'd)













22

Female O-Ring Fittings - Reduced Barrier















Female O-Ring Fittings - Reduced Barrier (cont'd)





Male Insert O-Ring Fittings - Standard Barrier





Male O-Ring Fittings - Standard Barrier















Male O-Ring Fittings - Standard Barrier (cont'd)







ATCO Beadlock Fittings

Male O-Ring Fittings - Reduced Barrier







Splicer Fittings - Standard Barrier









Splicer Fittings - Reduced Barrier



Weld-On Fittings - Standard Barrier


| Straight Weld-On Fitting (Standard Barrier) | | | |
|---|---|-------------------------|------------|
| | | (I | 0 |
| Fitting Size: No. 6 | Fitting Thread Size: 3/8" Tube | Hose Size: No. 6 | 1001338290 |
| Fitting Size: No. 8 | Fitting Thread Size: 1/2" Tube | Hose Size: No. 8 | 1001338301 |
| Fitting Size: No. 10 | Fitting Thread Size: 5/8" Tube | Hose Size: No. 10 | 1001338564 |
| Fitting Size: No. 12 | Fitting Thread Size: 3/4" Tube | Hose Size: No. 12 | 1001338581 |


Weld-On Fittings - Reduced Barrier











INCORRECT BUBBLE CRIMP OVER CRIMPING
Can damage inner lining and/or fitting due to over torque or wrong size crimping die selection.


FERRULE IS CRUSHED WITH METAL TABS EXTRUDING

FITTING HAS COLLAPSED INSIDE AND WILL RESTRICT FLOW

INCORRECT BUBBLE CRIMP

UNDER CRIMPING Can cause hose to blow off fitting due to wrong die size selection or under crimping. Typically hose will rotate easily if fitting is under crimped. ONLY A SLIGHT IMPRESSION MADE BY THE CRIMPING JAWS ABLE TO TWIST HOSE INSIDE FERRULE

INCORRECT BUBBLE CRIMP





Beadlock Fitting Identification

CRIMPING PROCEDURES FOR TYPICAL MOBILE REFRIGERATION HOSE:

- STEP 1 Determine hose size needed. (See "Beadlock Fitting Identification", "Goodyear (Galaxy) Hoses" on page 18.)
- STEP 2 Determine hose fitting size and type needed.



BARBED TYPE

SEPARATE FERRULE

TYPE B ONE PIECE FITTING



STEP 3 Make certain that the end of hose to be crimped is cut evenly.



CORRECT EVEN CUT



INCORRECT ANGLED CUT



INCORRECT ANGLED CUT

STEP 4 Push hose ALL the way into ferrule until hose is flush with peephole at the end of the ferrule.



CORRECT DEPTH



INCORRECT DEPTH

NOTE: It may be necessary to lubricate the hose inside diameter and/or hose fitting barbs

STEP 5 Determine correct crimping die size to match hose and fitting size. There are basically two types of crimp styles (see below).

FACE LONG CRIMP



TYPICALLY UTILIZED WITH 2 PIECE TYPE FITTINGS AND ALL RUBBER HOSE

BUBBLE CIRCULAR CRIMP




TYPICALLY UTILIZED WITH 1 PIECE BEADLOCK TYPE FITTINGS AND BARRIER NYLON/RUBBER HOSE

STEP 6 Crimp hose/fitting based on specific crimping machine manufacturer's recommendations. Reference the following illustrations for some common examples of correct and incorrect crimping.


Beadlock Fitting Identification


Male O-Ring






7/8"-18 Thread











Female O-Ring















Male Insert O-Ring









O-Rings














31


Female Flare










Beadlock Fitting Identification




Male Flare











Hose End Sizes






Torque Recommendations

| FLARE CONNECTIONS | | |
|-------------------|-------------|---------|
| Tube O.D. | Thread Size | Ft./Lb. |
| 3/8" | 5/8" | 18-20 |
| 1/2" | 3/4" | 36-39 |
| 5/8" | 7/8" | 52-57 |
| 3/4" | 11/16" | 71-79 |




Beadlock Fitting Identification


Refrigerant Hose Sizes




Beadlock




3/8" FITTING FOR NO. 6 HOSE



5/8" FITTING FOR NO. 10 HOSE





Torque Recommendations

| FLARE CONNECTIONS | | |
|-------------------|-------------|---------|
| Tube O.D. | Thread Size | Ft./Lb. |
| 3/8" | 5/8" | 18-20 |
| 1/2" | 3/4" | 36-39 |
| 5/8" | 7/8" | 52-57 |
| 3/4" | 11/16" | 71-79 |

| O-RING CONNECTIONS | | |
|--------------------|-------------|---------|
| Tube O.D. | Thread Size | Ft./Lb. |
| 3/8" | 5/8" | 11-13 |
| 1/2" | 3/4" | 15-20 |
| 5/8" | 7/8" | 21-27 |
| 3/4" | 11/16" | 28-33 |



Goodyear (Galaxy) Hoses

- This hose meets J2064 specification
- **Easy Couplability**

Internal rubber layer makes coupling simple, assuring better assembly integrity while reducing the risk of refrigerant loss around the fittings.

- **Reduced Ozone Permeation**
 - Internal Nylon Barrier hose is specifically designed to reduce the permeation level of ozone depleting refrigerant and chemicals in heavy duty air conditioning systems.
- **Universal Compatibility**

Extensive testing has shown 4826 Barrier Hose to be compatible with R-12, R-134a and Ternary Blends.

Low Volumetric Expansion

NOTE: For use with steel or aluminum Push-On or Beadlock (Bubble Crimp) type fittings only!

- Dimensionally Stable
- Flexible
- Easy to Route
- Reduction in Noise & Vibration
- J51 All Outside Diameters
- Tube: Polychloropene Barrier
- Reinforcement: Synthetic Yarn
- Cover: EPDM

| | ar (Galax d Fitting | ky) 4826 | Hose for |
|--|--|--|------------|
| Length: 50 Ft. Hose Size: No. 6 | Hose Inner Diameter: 5/16" (7.9mm) | Hose Outer Diameter: 3/4" (19.1mm) | 550307 |
| Length: 50 Ft. Hose Size: No. 8 | Hose Inner Diameter: 13/32" (10.3mm) | Hose Outer Diameter: 29/32" 23mm) | 550308 |
| Length: 50 Ft. Hose Size: No. 10 | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 1" 25.4mm) | 550309 |
| Length: 50 Ft. Hose Size: No. 12 | Hose Inner Diameter: 5/8" (15.9mm) | Hose Outer Diameter: 1 1/8" (28.6mm) | 550310 |
| Length: 825 Ft. Hose Size: No. 6 | Hose Inner Diameter: 5/16" (7.9mm) | Hose Outer Diameter: 3/4" (19.1mm) | 1002300977 |
| Length: 725 Ft. Hose Size: No. 8 | Hose Inner Diameter: 13/32" (10.3mm) | Hose Outer Diameter: 29/32" 23mm) | 1002301587 |
| Length: 700 Ft. Hose Size: No. 10 | Hose Inner Diameter: 1/2" (12.7mm) | Hose Outer Diameter: 1" 25.4mm) | 1002301589 |

Goodyear (Galaxy) 4890 Hose for Reduced Fitting Length: 50 Ft. Inner Outer Diameter: Diameter: 1001639549 Hose Size: (7.9 mm)(14.7mm)Length: 50 Ft. Hose Hose Outer Inner Diameter: Diameter: 1001639551 Hose Size: No. 8 13/32" (10.3mm) 11/16" (17.3mm) Length: 50 Hose Hose Outer Inner Diameter: 1/2" Diameter: 1001639552 Hose Size: No. 10 (12.7mm) (19.4mm) Length: 50 Ft. Hose Hose Outer Diameter: 15/16" Inner 1001639553 Diameter: 5/8" Hose Size: No. 12 (15.9mm) (23.6mm)Length: 825 Ft. Hose Hose Inner Outer 1001260067 Diameter: Diameter: Hose Size: No. 6 (7.9mm)(14.7mm) Hose Outer Length: 600 Ft. Hose Inner Diameter: Diameter: 1002300971 Hose Size: No. 10 1/2" (12.7mm) 3/4" (19.4mm) Length 600 Ft. Hose Hose Inner Outer Diameter: Diameter: 1001260075 Hose Size: 1/2" (12.7mm) No. 10 (19.4mm) Length 425 Ft. Hose Outer Hose Inner Diameter: 15/16" Diameter: 5/8" 1002300976 Hose Size: No. 12 (15.9mm) (23.6mm) Length: 425 Ft. Hose Hose Inner Outer Diameter: 5/8" Diameter: 15/16" 1001260076

🍪 Bergstrom.

Hose Size: No. 12

(15.9mm)

(23.6mm)




Burgaflex Fittings - Standard Barrier















Burgaflex Fittings - Reduced Barrier














Burgaflex Crimp Fittings - Reduced Barrier















Burgaflex Accessories









Ferrule Fittings



O-Rings



580565



O 570120

0





0

564700























NOTE: All O-Rings are shown actual size and packaged in quantities of 25



Slim line seal used in Freightliner applications (Packaged in quantities of 10)

| Part No | Description | OEM No. |
|------------|------------------|----------------|
| 1000039205 | Slim Line No. 6 | ABP N83 312076 |
| 1000039326 | Slim Line No. 8 | ABP N83 312060 |
| 1000039333 | Slim Line No. 10 | ABP N83 312092 |



Mini Stat seals used in Freightliner applications (Packaged in quantities of 10)

| Part No | Description | OEM No. | Color |
|------------|------------------|----------------|-------|
| 1000039445 | Mini Stat No. 6 | ABP N83 312366 | Red |
| 1000039471 | Mini Stat No. 8 | ABP N83 312368 | Red |
| 1000039483 | Mini Stat No. 10 | ABP N83 312361 | Red |
| 1000039492 | Mini Stat No. 12 | ABP N83 312372 | Red |
| 1002508370 | 1 in. Stat Seal | | |

O-Rings Specifications*

| Description/Applications | Part No | Material |
|--|------------|-------------------|
| No. 6 Hose Filter Dryer O-Ring, Ford No. 6 Springlock & Tube Fitting O-Ring, Ford Combination Valve Schrader Port | 570120 | Green HNBR |
| O-Ring, GM VIR Pickup Tube O-Ring, Nissan No. 10 Hose Fitting & Filter Dryer O-Ring, Nissan 10mm Filter Dryer, Condenser O-Ring, Ford Expansion Valve O-Ring, GM DA6 Discharge Crossover O-Ring, Mazda No. 6 Springlock Fitting O-Ring, Diesel Kiki BH DKS13G Oil Plug O-Ring, Min. Pressure Relief Valve O-Ring, Volvo No. 6 Hose Fitting O-Ring, | 580123 | Black Neoprene |
| Hyundai No. 6 Springlock O-Ring | 1002487275 | Yellow HNBR |
| No. 6 Compression Fitting O-Ring, Chrysler 6C17 Large Control Valve (Inner) O-Ring, York & Sanden Oil Plug O-Ring, GM Pressure Relief Valve O-Ring, Toyota Pressure Switch O-Ring, GM V5 Control Valve O-Ring, GM R-134a Two Piece 16mm Primary Seal O-Ring, Chrysler 6C17 Oil Plug & Pressure Relief Valve O-Ring, GM, Ford Pressure Cycling Switch O-Ring, Sanden Compressor 1/4" Service Port O-Ring, Mitsubishi FX105V Compressor Control Valve (Inner) O-Ring, GM In-Line Filter O-Ring, Volvo Cycling/Pressure Switch O-Ring | 580113 | Black Neoprene |
| No. 8 Hose Fitting O-Ring, Ford No. 8 Tube Fitting & Non-metric Springlock O-Ring, Volvo No. 8 Hose Fitting O-Ring, Mazda | 564700 | Green HNBR |
| No. 8 Springlock Fitting O-Ring, GM V5 Control Valve O-Ring, Nissan No. 12 Hose Fitting & Condenser Discharge Line O-Ring, Nissan 12mm STV Valve, Filter Dryer, Condenser, Hose Fitting O-Ring, GM VIR Inlet Fitting O-Ring, Toyota Discharge Line O-Ring, Aeroquip Two Piece 13mm R-134a Adapter O-Ring, Mazda O-Ring, Hyundai No. 8 Springlock O-Ring, Mitsubishi Hose Fitting O-Ring | 580124 | Black Neoprene |
| No. 10 Hose Fitting O-Ring, Ford No. 10 Tube Fitting & Non-metric Springlock O-Ring, Nissan Evaporator Suction Fitting | 572770 | Green HNBR |
| O-Ring, Nissan 16mm STV Valve, Evaporator, Hose Fitting O-Ring, Toyota Suction Line O-Ring, Volvo No. 10 Hose Fitting O-Ring, Mitsubishi Hose Fitting O-Ring, Nippondenso TV Manifold Port O-Ring, Nippondenso TV10/TV12C/TV14C Sensor Housing O-Ring, Mazda Hose Fitting O-Ring, York, Tecumseh Tube-O Valve O-Ring, Aeroquip Two Piece 16mm Adapter O-Ring | 580125 | Black Neoprene |
| No. 12 Hose Fitting O-Ring, Ford No. 12 Tube Fitting & Non-metric Springlock O-Ring, VIR Expansion Valve Lower O-Ring, | 580114 | Green HNBR |
| VIR Evaporator Fitting Outlet O-Ring, VIR Connection to Evaporator Suction Line O-Ring, GM V5 Control Valve O-Ring, Chrysler 6C17 Small Control Valve O-Ring, Volvo No. 12 Hose Fitting O-Ring, Nissan 19mm Evaporator Suction O-Ring | 580210 | Black Neoprene |
| No. 8 GM Captive O-Ring, Chrysler 6C17 Large Control Outer O-Ring | 580089 | Black Neoprene |
| No. 10 GM Captive O-Ring, GM DA6, Sanden SD505/507/TR70/TR90 Compressor Shaft Seal Head O-Ring, Hitachi Compressor Crossover O-Ring, Matsushita Compressor Model S1150 Carbon Seal Head O-Ring | 580092 | Black Neoprene |
| No. 12 GM Captive O-Ring, GM A6, R4, Sanden SD708/709 Compressor Shaft Seal Head O-Ring, Mitsubishi Compressor Model FX80 Suction Port O-Ring, Nihon Compressor Model DKV14C Carbon Seal O-Ring | 580091 | Black Neoprene |
| 5/8" O-Ring, Water, Antifreeze | 1000233458 | Black EPDM |
| O-Ring | 580565 | Green HNBR |
| OTAIIS | 1002487273 | Yellow HNBR |
| O-Ring, Water Valve Fitting | 589640 | HQ Nitrile |
| 1 in HNBR O-Ring | 1002508371 | HNBR |
| 1.84 in HNBR O-Ring | 1000259338 | HNBR |

 $^{^{\}star}\,$ All o-rings purchased separately are packaged in quantities of 25.



O-Rings

O-Ring Assortment Kits


| Description | Part No |
|---------------------------------|---------|
| O-Ring & Service Assortment Kit | 550367 |



NOTE: Complete kit may be ordered by Part Number 2799201. Individual parts may be ordered by referencing the part number for each item as listed in the table (to ight).

| Part No | Qty. | Description |
|---------|------|---|
| | 7 | GM Compressor Port O-Ring, Black Neoprene |
| 580089 | 7 | No. 8 GM Captured O-Ring, Black Neoprene |
| 580125 | 7 | No. 10 Hose Fitting O-Ring, Black Neoprene |
| | 7 | Equalizer Tube O-Ring, Black Neoprene |
| 580124 | 7 | No. 8 Hose Fitting O-Ring, Black Neoprene |
| 580091 | 7 | No. 12 Captured Fitting O-Ring, Black Neoprene |
| | 7 | No. 6 Captured O-Ring, Black Neoprene |
| 580210 | 7 | No. 12 Hose Fitting O-Ring, Black Neoprene |
| 570120 | 7 | No. 6 Hose Fitting O-Ring, Green HNBR |
| | 10 | CCI & Tecumseh Rotolock Service Valve Teflon Seal |
| | 3 | CCI & Tecumseh Long Stem Cap |
| 580108 | 10 | Charging Port Cap (3/16") |
| | 10 | Service Valve Cap (1/4") |
| | 1 | A-6 Shaft Nut |
| | 1 | Washer |
| | 10 | Charging Hose Seal |
| 580099 | 10 | Charging Hose Depressor |

| Description | Part No |
|---------------------------|---------|
| Job O-Ring Assortment Kit | 525674 |



Kit Contents:

550403

10

3

Kit Contents:

| Qty. | Description |
|------|---------------|
| 1 | O-Ring No. 4 |
| 7 | O-Ring No. 6 |
| 6 | O-Ring No. 8 |
| 4 | O-Ring No. 10 |
| 1 | O-Ring No. 12 |

Can Tap Seal Gasket

Sanden Shaft Key

Schrader Valve Core

CCI & Tecumseh Compressor Woodruff Key

| Sentence Sent-Port (s. Prop. Serve) | No. 679-100 Smary Softens | No. of Stead Prints Orders | the better them. |
|--|--------------------------------------|--|--|
| Name to Address of the Party of | Maso No. 5 San Shing San Shing | Steam No. 10 Steam Printed Steam String | Manager Str. 10 Street Street Containing Street |
| Separate Separate | 1000 | Street St | 2000 To 1000 T |

Kit Contents:

| Part No | Description |
|---------|--|
| | Compressor Switch Port Oil Plug O-Ring, Black Neoprene |
| 564700 | No. 8 Hose Fitting O-Ring, Green HNBR |
| 572770 | No. 10 Hose Fitting O-Ring, Green HNBR |
| | No. 5 (7MM) Toyota Fitting Seal |
| | Nissan No. 8 Hose Fitting/Drier O-Ring |
| 570120 | Nissan No. 10 Hose Fitting/Drier O-Ring, Green HNBR |
| 580125 | Nissan Evaporator Suction Line O-Ring, Green HNBR |
| 580565 | Nissan Condenser Liquid Line O-Ring |
| 580124 | Nissan Compressor Flange O-Ring, Green HNBR |

Qty. 10 each per complete kit.

O-Ring Assortment Kits (cont'd)

Description Part No Freightliner Stat Seal & Sealing Washer Assortment Kit 1002430992



| Kit Contents: | |
|---------------|---|
| Part No | Description |
| 1000039205 | No. 6 Slim Line Washer, Black |
| 1000039326 | No. 8 Slim Line Washer, Black |
| 1000039333 | No. 10 Slim Line Washer, Black |
| 1000039445 | No. 6 Mini Stat Seal Washer, Red |
| 1000039471 | No. 8 Mini Stat Seal Washer, Red |
| 1000039483 | No. 10 Mini Stat Seal Washer, Red |
| 1000039492 | Comp. Suction/Discharge Mini Stat Seal, Red |
| 1002508370 | No. 12 Mini Stat Seal Washer, Red |

Qty. 10 each per complete kit.

| Description | | | |
|--------------------------------|--|--|--|
| Master Deluxe O-Ring & Sealing | | | |
| Assortment Kit | | | |

Part No 1002431343



| Part No | Description | | |
|------------|--|--|--|
| 570120 | No. 6 GM/Ford, Chrysler/Import Hose Fitting O-Ring, Green HNBR | | |
| 564700 | No. 8 Ford Springlock Fitting O-Ring, Green HNBR | | |
| 572770 | No. 10 Ford Springlock Fitting O-Ring, Green HNBR | | |
| 580114 | No. 12 Ford Springlock Fitting O-Ring, Green HNBR | | |
| 1002487273 | Nissan Condenser Liquid Line O-Ring, Yellow HNBR | | |
| 1002487275 | No. 6 Hose Fitting O-Ring, Yellow HNBR | | |
| 550403 | Standard Flow Valve Core | | |
| 551354 | High Flow Valve Core | | |
| 550397 | High Flow Valve Core | | |
| 550398 | High Flow Valve Core | | |
| 1000417503 | 1/2 C-Plate Seal | | |
| 1000417507 | 3/4 C-Plate Seal | | |
| | High Flow M8 Valve Core | | |
| 1000039445 | Freightliner Drier/TXV No. 6 Stat Seal Washer | | |
| 1000039471 | Freightliner Drier/TXV No. 8 Stat Seal Washer | | |
| 1000039492 | Freightliner Compressor Suction/Discharge Stat Seal | | |
| 1000039483 | Freightliner Drier/TXV No. 10 Stat Seal Washer | | |
| 1002508370 | Freightliner No. 12 Suction Stat Seal | | |
| 550253 | R134a Low Side Cap, Blue | | |
| | R134a 13mm High Side Standard Flow Cap, Red | | |
| B360874 | 13mm High Flow Cap, Blue | | |
| 551112 | AC Discharge Cap, Red | | |
| 550399 | AC Charge Cap, Red | | |
| 550401 | 16mm Eaton Port Cap | | |

Qty. 2 each per complete kit.

O-Ring Kit Listing

| <u> </u> | | |
|---------------------------|---|---------|
| Kit Description | Contents | Part No |
| Metric O-Ring Kit | A complete assortment of green R-134a O-Rings. (shown on previous page) | 869437 |
| Deluxe O-Ring Kit | A complete assortment of O-Rings along with seals, gaskets, Schrader valves, expansion valve screens and caps for R-12 and R-134a. (shown on previous page) | 550367 |
| Job O-Ring Assortment Kit | Various size o-rings (shown on previous page) | 525674 |



Bulkhead Adapters, Tubing & Drain Hoses

O-Ring Assortment Kits (cont'd)

O-Ring Kit Listing

| Kit Description | Contents | Part No |
|--|---|------------|
| Freightliner Stat Seal & Sealing Washer Assortment Kit | An assortment of slimline washers and stat seals | 1002430992 |
| Master Deluxe O-Ring & Sealing Washer Assortment Kit | A complete assortment of O-Rings, valve cores, c-plates, stat seals and washers | 1002431343 |

O-Ring Rubber Material Data

| o material bata | | |
|---|------------------------------|---|
| Rubber Type / Designation | Color | Automotive Application |
| Nitrile Buna / Buna N / NBR (Nitrile Butadiene Rubber) | Black | AC Systems with R-12 Refrigerant & Mineral Oil Power Steering / Rack & Pinion Systems Heater Systems Fuel Systems |
| HSN (Highly Saturated Nitrile) / HNBR (Hydrogenated Nitrile Butadiene Rubber) | Green or Yellow | AC Systems with R-12 Refrigerant & Mineral Oil AC Systems with R-134a Refrigerant & PAG (Polyalkylene Glycol) or POE (Polyol Ester) Refrigerant Oils |
| Neoprene / CR (Chloroprene Rubber) | Black, Red or Blue Tinted | Same as above |

Bulkhead Adapters





Bulkhead Adapters, Tubing & Drain Hoses

Drain Hose & Accessories



General Specifications: Drain Tube





















2


Bulkhead Adapters, Tubing & Drain Hoses Insulation Tubing






Tube & Fitting Assembly














Ducting, Clamps & Hoses

Flexible Ducting



Hose Clamps





General Specifications: Double hose clamp

Clamp Inner Diameter: 2" max.

Part No: 1003389790 (packaged in quantities of 10)



General Specifications: Cable clamp

Clamp Inner Diameter: 3/16"max.

Hose/Duct Clamp (packaged in quantities of 25)



| Fitting Size: .56" (14.22mm) | Clamp Inner Diameter: 1/2" min. to 1" max. | B290214 |
|-------------------------------|---|---------|
| | Clamp Inner Diameter: 5/8" min. to 1 1/4" max. | B290304 |
| Fitting Size: 3.12" (79.25mm) | Clamp Inner Diameter: 3" min. to 4 1/4" max. | B290303 |



Accessories Hoses











Wire Clips & Ties

